

SAFETY DATA SHEET

Goof Off Heavy Duty Remover 4 oz.

Page: 1

Revision: 07/20/2017
Supersedes Revision: 05/04/2015

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Goof Off Heavy Duty Remover 4 oz.
Company Name: W. M. Barr
2105 Channel Avenue
Memphis, TN 38113
Phone Number: (901)775-0100

Web site address: www.wmbarr.com

Emergency Contact: 3E 24 Hour Emergency Contact (800)451-8346
Information: W.M. Barr Customer Service (800)398-3892

Intended Use: Mult-Purpose Remover for tar, ink, paint, adhesive, etc.

Product Code: FG705, FG705E

Additional Information This product is regulated by the United States Consumer Product Safety Commission and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to using the product.

2. HAZARDS IDENTIFICATION

Serious Eye Damage/Eye Irritation, Category 1

Skin Sensitization, Category 1



GHS Signal Word: Danger

GHS Hazard Phrases: H317: May cause an allergic skin reaction.
H318: Causes serious eye damage.


GHS Precaution Phrases: P261: Avoid breathing gas/mist/vapors/spray.
P272: Contaminated work clothing should not be allowed out of the workplace.
P280: Wear protective gloves/protective clothing/eye protection/face protection.

GHS Response Phrases: P302+352: IF ON SKIN: Wash with plenty of soap and water.
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310: Immediately call a POISON CENTER or doctor/physician.
P321: Specific treatment see label.
P333+313: If skin irritation or rash occurs, seek medical advice/attention.
P363: Wash contaminated clothing before reuse.

GHS Storage and Disposal Phrases: P501: Dispose of contents/container according to local, state and federal regulations.

Hazard Rating System:

HEALTH	*	1
FLAMMABILITY		1
PHYSICAL		0
PPE		X



NFPA:

HMIS:

OSHA Regulatory Status: This material is classified as hazardous under OSHA regulations.

SAFETY DATA SHEET

Goof Off Heavy Duty Remover 4 oz.

Page: 2

Revision: 07/20/2017
Supersedes Revision: 05/04/2015

Potential Health Effects (Acute and Chronic):

Eyes:

May cause severe irritation, experienced as discomfort or pain, excess blinking and tear production, marked excess redness and swelling of the conjunctiva, and chemical burns of the eye.

Skin:

May cause moderate skin irritation. Prolonged and/or repeated contact may cause defatting of the skin and dermatitis. Causes redness and pain. May be harmful if absorbed through the skin.

Inhalation:

When used as directed, the consumer is not expected to experience any exposure effects. Excessive exposure may cause irritation to the upper respiratory tract. Symptoms may include a headache, dizziness, or nausea.

Ingestion:

Harmful if swallowed. May cause severe gastrointestinal tract irritation with nausea, vomiting and possible burns. May produce signs of intoxication characterized by incoordination, dizziness, drowsiness, headache, nausea, mental confusion, possibly slurred speech, and stupor.

Chronic Health Effects:

Diethylene glycol monobutyl ether has caused red blood cell hemolysis in laboratory animals and secondary injury to the kidney and liver. However, humans appear to be resistant to this effect.

Prolonged skin contact may cause dermatitis.

Target Organs: Blood (Hemolysis), Kidneys, Liver, Central Nervous System.

Primary Routes of Entry: Inhalation, Ingestion

Medical Conditions Generally None known.

Aggravated By Exposure:

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS #	Hazardous Components (Chemical Name)	Concentration
100-51-6	Benzenemethanol {Benzyl alcohol}	<10.0 %
2568-90-3	1,1'-[Methylenebis(oxy)]dibutane	<10.0 %
27177-77-1	Benzenesulfonic acid, dodecyl-, potassium salt	<10.0 %
112-34-5	Diethylene glycol monobutyl ether {2-(2-Butoxyethoxy)ethanol {(a glycol ether)}}	< 5.0 %

Additional Chemical Information

Specific percentage of composition is being withheld as a trade secret.

4. FIRST AID MEASURES

Emergency and First Aid Procedures:	Skin: Remove contaminated clothing. Immediately wash skin thoroughly with large amounts of water and mild soap, if available. Seek medical attention if irritation develops or persists. Eyes: Immediately begin to flush eyes with water, remove any contact lens. Continue to flush the eyes for at least 15 minutes. Seek medical attention. Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Ingestion: If swallowed, do NOT induce vomiting. Seek immediate medical attention. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.
Signs and Symptoms Of Exposure:	See Potential Health Effects.
Note to Physician:	Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.

5. FIRE FIGHTING MEASURES

Flash Pt:	No data.	
Explosive Limits:	LEL: No data.	UEL: No data.
Autoignition Pt:	No data.	
Suitable Extinguishing Media:	Non-combustible liquid - use extinguishing media for underlying cause of fire.	
Unsuitable Extinguishing Media:	None known.	
Fire Fighting Instructions:	Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.	
Flammable Properties and Hazards:	Flashpoint: No flash to boiling. This material does not exhibit a flashpoint per the Setaflash Closed Cup test method.	

6. ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case Material Is Released Or Spilled:	Prevent entry into waterways, sewers, or confined areas. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to compatible containers for proper disposal. For large spills, dike ahead of the spill.
-------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

7. HANDLING AND STORAGE

Precautions To Be Taken in Handling:	Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. A source of clean water should be kept in the immediate work area for flushing of the eyes and skin. Follow all MSDS/label precautions even after container is emptied because they may retain product residues.
Precautions To Be Taken in Storing:	Keep containers closed when not in use. Store in a cool, dry place, out of direct sunlight. Protect from freezing.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
100-51-6	Benzenemethanol {Benzyl alcohol}	No data.	No data.	No data.
2568-90-3	1,1'-[Methylenebis(oxy)]dibutane	No data.	No data.	No data.
27177-77-1	Benzenesulfonic acid, dodecyl-, potassium salt	No data.	No data.	No data.
112-34-5	Diethylene glycol monobutyl ether {2-(2-Butoxyethoxy)ethanol {(a glycol ether)}	No data.	No data.	No data.

- Respiratory Equipment (Specify Type):** When used by the consumer following directions for use and with adequate ventilation, respiratory protection is not expected to be needed.
- A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.
- If the work area is not properly ventilated to keep airborne levels below their exposure limits, you must use a properly fitted and maintained NIOSH approved respirator for organic vapors. A dust mask does not provide protection against vapors.
- Eye Protection:** Where contact with the eyes or face is likely from spraying or splashing, safety glasses, a faceshield or chemical goggles should be worn to prevent eye contact.
- Protective Gloves:** When used as directed, protective gloves should not be required. For prolonged or repeated contact, wear gloves with as much resistance to the chemical ingredients as possible. Glove materials such as natural rubber or nitrile rubber provide protection. Glove selection should be based on chemicals being used and conditions of use. Consult your glove supplier for additional information.
- Other Protective Clothing:** Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure.
- Engineering Controls (Ventilation etc.):** Ventilation is normally not required when handling or using this product to keep exposure to airborne contaminants below the exposure limit.
- Good general ventilation should be sufficient to control airborne levels.
- Work/Hygienic/Maintenance Practices:** Wash hands thoroughly after use and before eating, drinking, smoking, or using the restroom.
- Do not eat, drink, or smoke in the work area.
- Discard any clothing or other protective equipment that cannot be decontaminated.
- Facilities storing or handling this material should be equipped with an emergency eyewash and safety shower.

SAFETY DATA SHEET
Goof Off Heavy Duty Remover 4 oz.

Page: 5

Revision: 07/20/2017
Supersedes Revision: 05/04/2015

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical States: [] Gas [X] Liquid [] Solid
Appearance and Odor: Clear, thin, colorless to light yellow liquid.
Melting Point: 32.00 F
Boiling Point: 212.00 F
Autoignition Pt: No data.
Flash Pt: No data.
Explosive Limits: LEL: No data. UEL: No data.
Specific Gravity (Water = 1): 1.0022
Density: 8.34 LB/GL
Vapor Pressure (vs. Air or mm Hg): No data.
Vapor Density (vs. Air = 1): > 1
Evaporation Rate: > 1
Solubility in Water: Complete
pH: 6.5 - 7.5
Percent Volatile: 92.0 % by weight.
VOC / Volume: 9.0000 % WT

10. STABILITY AND REACTIVITY

Stability: Unstable [] Stable [X]
Conditions To Avoid - Instability: None known.
Incompatibility - Materials To Avoid: Strong alkalies, acids, and oxidizers.
Hazardous Decomposition or Byproducts: Carbon monoxide, carbon dioxide
Possibility of Hazardous Reactions: Will occur [] Will not occur [X]
Conditions To Avoid - Hazardous Reactions: None known.

SAFETY DATA SHEET
Goof Off Heavy Duty Remover 4 oz.

11. TOXICOLOGICAL INFORMATION

Toxicological Information: Product has not been tested as a whole, Refer to section 2 for acute and chronic health effects.

CAS# 112-34-5:

Standard Draize Test, Eyes, Species: Rabbit, 20.00 MG, Severe.

Result:

Behavioral: Anticonvulsant.

- American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave., Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
100-51-6	Benzenemethanol {Benzyl alcohol}	n.a.	n.a.	n.a.	n.a.
2568-90-3	1,1'-[Methylenebis(oxy)]dibutane	n.a.	n.a.	n.a.	n.a.
27177-77-1	Benzenesulfonic acid, dodecyl-, potassium salt	n.a.	n.a.	n.a.	n.a.
112-34-5	Diethylene glycol monobutyl ether {2-(2-Butoxyethoxy)ethanol {(a glycol ether)}	n.a.	n.a.	n.a.	n.a.

12. ECOLOGICAL INFORMATION

General Ecological Information: Product has not been tested as a whole.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose of in accordance with all applicable local, state, and federal regulations. Do not dump into sewers or allow to enter waterways.

14. TRANSPORT INFORMATION

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Not regulated by D.O.T.

DOT Hazard Class:

UN/NA Number:

Additional Transport Information:

15. REGULATORY INFORMATION

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
100-51-6	Benzenemethanol {Benzyl alcohol}	No	No	No
2568-90-3	1,1'-[Methylenebis(oxy)]dibutane	No	No	No
27177-77-1	Benzenesulfonic acid, dodecyl-, potassium salt	No	No	No
112-34-5	Diethylene glycol monobutyl ether {2-(2-Butoxyethoxy)ethanol {(a glycol ether)}	No	No	Yes-Cat. N230

This material meets the EPA Yes No Acute (immediate) Health Hazard

'Hazard Categories' defined Yes No Chronic (delayed) Health Hazard

for SARA Title III Sections Yes No Fire Hazard

311/312 as indicated: Yes No Sudden Release of Pressure Hazard

Yes No Reactive Hazard

SAFETY DATA SHEET

Goof Off Heavy Duty Remover 4 oz.

Page: 7

Revision: 07/20/2017
Supersedes Revision: 05/04/2015

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
100-51-6	Benzenemethanol {Benzyl alcohol}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
2568-90-3	1,1'-[Methylenebis(oxy)]dibutane	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
27177-77-1	Benzenesulfonic acid, dodecyl-, potassium salt	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
112-34-5	Diethylene glycol monobutyl ether {2-(2-Butoxyethoxy)ethanol {(a glycol ether)}	CAA HAP,ODC: Yes - Cat.; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No

Regulatory Information Statement: All components of this material are listed on the TSCA Inventory or are exempt.

16. OTHER INFORMATION

Revision Date: 07/20/2017
Preparer Name: W.M. Barr EHS Dept (901)775-0100

Additional Information About This Product: No data available.

Company Policy or Disclaimer: The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.